



# Product Listing

## March 2011

The Penrite Oil Company is 100% Australian family owned and is one of Australia's largest independent oil companies. Established in 1926, it is a market leader in producing high performance lubricants for the enthusiast and everyday motorist alike. The Company's success is attributed to its technical excellence in formulating quality lubricants specifically to meet Australian conditions.

### HPR PREMIUM PERFORMANCE ENGINE OILS – WITH FULL ZDDP

Penrite HPR premium engine oils are a range of products designed to lubricate all passenger vehicles from modern everyday compact and family cars to high performance cars, light commercials (<3.5MT GVM), 4WD's and modern four stroke motorcycles. Designed for Australian conditions, they provide complete protection for your engine no matter what you drive or where you are.

#### HPR 0

Semi-synthetic oil designed for use where SAE 0W-20 and 5W-20 petrol or diesel oils are specified in the vehicle owner's handbook and the fuel economy ACEA A1/B1 and A5/B5 oils are recommended for use such as in Volvo and Chrysler. May also be used where ILSAC GF-3 and GF-4 is required. Vehicles fitted with DPFs must use Enviro+, Diesel LA or Diesel SP as appropriate.

SAE 0W-30, API CH-4/SL, ACEA A3/B4.

*Package and Code:*

5LHPRD5005                      20L HPRD5020                      205L HPRD5205

#### HPR 5

Semi-synthetic engine oil for use in the latest generation of high performance engines. Ideal where this viscosity or SAE 5W-30 or 10W-30 oils are recommended. Particularly suited for engines with variable valve timing as well as where ILSAC GF-3/GF-4 and ACEA A1/B1, A5/B5 fuel economy oils are called for.

SAE 5W-40, API SN/CF, ACEA A3/B4, Ford M2C 912/913, MB229.3

*Package and Code:*

1L HPR05001                      5L HPR05005    20L HPR05020                      60L HPR05060                      205L HPR05205

#### HPR 10

Semi-synthetic wide range viscosity engine oil developed to give the optimum balance between engine protection and fuel economy/power retention. Recommended for use in a wide range of vehicles built since 1996 including those that require 10W-xx and 15W-40 grade oils.

SAE 10W-50, API SN/CF, ACEA A3/B4, M2C902/910, HN2100, MB229.3

*Package and Code:*

1L HPR10001                      5L HPR10005                      20L HPR10020                      60L HPR10060                      205L HPR10205

#### HPR 15

Semi-synthetic engine oil formulated primarily for use in "older" engines that require SAE 15W-40 or 15W-50 grades such as pre 1997 Australian family cars. Not recommended for motorcycles.

SAE 15W-60, API SN/CF, ACEA A3/B4, M2C 153E, Opel B0401013

*Package and Code:*

1L HPR15001                      5L HPR15005                      20L HPR15020                      60L HPR15060                      205L HPR15205

#### HPR 30

Formulated for use in conventional engines operating under a high load environment. It provides better oil pressure and consumption control where SAE 20W-50 oils were originally recommended.

SAE 20W-60, API SM/CF, ACEA A3/B3, M2C 153G

*Package and Code:*

1L HPR30001                      5LHPR30005                      20L HPR30020                      60L HPR30060                      205L HPR30205

#### HPR 40

High viscosity petrol engine oil for use in larger capacity engines where climatic temperatures necessitate an oil of a higher viscosity or where oil consumption is becoming an issue with lighter viscosity grades. Also recommended for selected older large capacity petrol engines fitted with aftermarket turbochargers and in large capacity competition engines.

25W-70, API SL

*Package and Code:*

1L HPR40001                      5LHPR40005                      20L HPR40020                      60L HPR40060                      205L HPR40205

#### HPR 50

Extra high viscosity petrol engine oil for use in older large six and eight cylinder engines especially those subjected to heavy/extreme load situations such as caravan/boat towing or in competition. Equally suitable for large capacity engines with severe oil consumption problems.

40-70, API SL

*Package and Code:*

1L HPR50001                      5LHPR50005                      20L HPR50020                      60L HPR50060                      205L HPR50205



## EVERYDAY DRIVING MOTOR OILS

Value brand mineral motor oils suitable for general-purpose applications in mid range petrol and diesel fuelled motor vehicles. Available in four grades. The 5W-30 grade is ideal for the Mazda RX-8 and other vehicles that require this grade and the 10W-30 for other modern vehicles that use API SL or GF-3 engine oils. The 15W-40 grade is designed for vehicles in good condition built from about 1990 and the 20W-50 grade for vehicles in good condition built before 1990. All grades meet the requirements of JASO MA so can be used in four stroke motorcycles with wet clutches. 30-70 STOPS OIL BURNING is a value brand motor oil suitable for older vehicles suffering from oil consumption due to high wear.

### Package and Code:

	<b>5W-30 (SL/CF/GF-3/MA)</b>	<b>10W-30 (SL/CF/GF-3/MA)</b>
5L	PMO05005	PMO10005
	<b>15W-40 (SL/CF-4/GF-3/MA)</b>	<b>20W-50 (SL/CF-4/GF-3/MA)</b>
5L	PMO15005	PMO20005
	<b>30-70 (S.J)</b>	
5L	PMO3005	

## SIN EXTREME RANGE

### SIN ENGINE OILS – WITH FULL ZDDP

A range of engine oils designed using cutting edge technology for ultimate engine protection and performance. They may be used in most cars. The 0W-50, 15W-50 and 20W-60 grades are also ideal for four stroke motorcycles.

Sin Engine Oil 5 and 10 are premium fully synthetic oils blended with highly shear stable viscosity modifiers and additives. They exceed API SN/CF, ACEA A3/B4, BMW LL-01 and MB 229.5. SIN 0 uses only PAO and ester base oils. It exceeds API SN/CF, BMW-LL98, MB 229.1 and JASO MA.

### Package and Code:

	0 (SAE 0W-50)	5 (SAE 5W-60)	10 (MULTI 10W-70)
1L		SINE5001	SINE10001
5L	SINE0005	SINE5005	SINE10005
20L	SINE0020	SINE5020	SINE10020
205L	SINE0205	SINE5205	SINE10205

Sin Engine Oil 15 and 20 are premium full synthetic oils made from highly specialized shear-free base oils and additives. They exceed API SN/CF and ACEA A3/B4 and JASO MA.

### Package and Code:

	15 (SAE 15W-50)	20 (SAE 20W-60)
5L	SINE15005	SINE20005
20L	SINE15020	SINE20020

## SIN TWO STROKE OIL

Ultimate premium full synthetic, ester based two-stroke oil for high performance motorbikes, go karts and in other severe two stroke applications. It exceeds ISO EG-D and JASO FD. Biodegradable.

### Package and Code:

1L	SINTS001	20L SINTS020
----	----------	--------------

## SIN BRAKE FLUID

Fully synthetic, long life, high boiling point (over 300°C) fluid for maximum braking performance. Exceeds Super DOT 4.

### Package and Code:

500ml SINBF0005

## SIN GEAR OIL 75 AND 80

Premium full synthetic gear oils designed for maximum protection, life and performance. Exceeding API GL-5 and GL-6 they may be used in transmissions and differentials of all types of high performance cars. SIN Gear Oil 80 has been especially enhanced to survive the extremes of V8 operations. Full limited slip performance.

### Package and Code:

	75 (SAE 75W-90)	80 (SAE 80W-140)
2.5L	SING750025	2.5L SING800025
20L	SING75020	20L SING80020

## SIN RACE GEAR 110

Advanced mineral oil with synthetic-like heat resistance, designed for Race Gearboxes as well as differentials. In particular, it can be used to replace SAE 140 gear oils in differentials where its enhanced load carrying capacity can lower running temperatures due to the lower oil viscosity and friction reducing properties of the EP system. Can also replace SAE 90 oils where a thicker oil film is required for long distances or where severe shock loads may be encountered. Do not use if water contamination is expected.

### Package and Code:

20L SINRG110020

## SIN MANUAL TRANS

Full synthetic, special low viscosity gear oil designed for use in automotive and motorcycle gear boxes. Can improve cold shift performance. Meets API GL-4, MB 235.4 and SAE 75W-85.

### Package and Code:

2.5L SINMT0025	20L SINMT020	60L SINMT060
----------------	--------------	--------------



## MONO 30, 40 and 50 TRUCK

Mono 30 is a mid ash monograde engine oil for use in older Japanese four stroke engines and other engines used in off road applications. Mono 40 and 50 are low ash oils designed for use in Detroit Diesel two stroke engines and in engines that need heavier monograde oils. Mono 50 Truck may be used in manual transmissions requiring API GL-1 90 or CC/CD SAE 50 engine oils.

SAE 30, 40 and 50, API CF-2/CF/SF

*Package and Code:*

### MONO 30 MONO 40

20L MONO30020  
205L MONO3 0205

### MONO50

MONO40020  
MONO4 0205

MONO50020  
MONO50205

## DIESEL FX

High quality, heavy duty oil designed for use in mixed fleets and in many types of heavy and light duty diesel engines. Suitable for use in naturally aspirated and turbocharged diesel engines.

SAE 15W-40, API CI-4/SL, ACEA E7, MB 228.3, MAN 3275, Cummins 20076/77, Mack EO-M Plus

*Package and Code:*

20L DFX020

205L DFX205

## SMALL ENGINE OILS – FOUR STROKE

### FOUR STROKE MULTIGRADE SAE 10W-30

Non-friction modified semi-synthetic engine oil for use in modern small air and water-cooled petrol engines. Best suited for four stroke mowers, small stationary engines and other gardening equipment.

SAE 10W-30, API SL/CF, ACEA A3/B3

*Package and Code:*

1L SEFS1030001

2.5L SEFS10300025

20L SEFS1030020

205L SEFS1030205

### FOUR STROKE MONOGRADE SAE 30

A general-purpose monograde engine oil for small four stroke petrol engines particularly those with side valve configuration. Also recommended for use in many pre-1970 stationary diesel engines.

SAE 30, API SG/CD, MIL-L-2104B

*Package and Code:*

1L SEFS30001

2.5L SEFS300025

5L SEFS30005 20L

SEFS30020

205L SEFS30205

### FOUR STROKE MULTIGRADE SAE 20W-50

A general-purpose multigrade for small four stroke petrol engines particularly those with overhead valve configuration. It is suitable for use in many four-stroke motorcycles.

SAE 20W-50, API SG/CF, JASO MA (four stroke motorcycles)

*Package and Code:*

1L SEFS20W50001

2.5L SEFS20W500025

205L SEFS20W50205

## MARINE OUTBOARD FOUR STROKE ENGINE OIL

Premium multigrade semi-synthetic engine oil designed to offer the best protection against wear and salt water corrosion in marine outboard and in board engines. May also be used in four stroke motorcycles.

SAE 10W-50, NMMA FC-W<sup>®</sup> Performance, JASO MA, API SL

*Package and Code:*

2.5L MAR40025

10L MAR4010

205L MAR4205

## HD OIL

An extra high viscosity multigrade, high zinc, non-friction modified engine oil for use in older large capacity engines, including pre-Evolution Harley Davidsons.

50-70, API SF

*Package and Code:*

4L HD004 205L HD205

## ENDURO FOUR STROKE MOTORCYCLE OIL

Non-friction modified, high zinc engine oil for air and water-cooled engines. Ideal for Evolution engined Harley Davidsons and large capacity (greater than 600cc) European motorcycles, in high temperature operation and in high mileage units. Harley Davidson Twin Cam and post 1992 should use HPR Gas.

25W-70, JASO MA, API SG

*Package and Code:*

4L END004 20L END020

205L END205

## SMALL ENGINE OILS – TWO STROKE

### SIN TWO STROKE OIL

Ultimate full synthetic, ester based two-stroke oil for high performance motorbikes, go karts and in other severe two stroke applications. It exceeds ISO EG-D and JASO FD. Biodegradable.

*Package and Code:*

1L SINTS001

20L SINTS020

### HI-PER TWO STROKE OIL

High performance, semi-synthetic, low smoke oil suitable for warranty service in two stroke engines requiring API TC/JASO FC oils or higher. Mixes readily with petrol. Suitable for Sea Doo jet skis as well as in chainsaws operating under severe conditions.

ISO EG-C, API TC, JASO FC

*Package and Code:*

1L SEHPTS001

2.5L SEHPTS0025

20L SEHPTS020

## GREENKEEPERS TWO STROKE ENGINE OIL

Recommended for use by the home gardener or small business in motor mowers, brush cutters, hedge trimmers, agricultural and industrial two stroke power units. Mixes readily with petrol.

API TC/FB

*Package and Code:*

200ml SEGNKTS0002  
20L SEGNKTS020

1L SEGNKTS001  
205L SEGNKTS205

2.5L SEGNKTS0025

## GENERAL PURPOSE TWO STROKE OIL

Recommended for use by the home gardener or small business in motor mowers, brush cutters, hedge trimmers, agricultural and industrial two stroke power units. Mixes readily with petrol.

API TC/FB

*Package and Code:*

1L GPTS0001CB

## SYNMARINE OUTBOARD TWO STROKE OIL

Fully synthetic two stroke outboard engine oil suitable for premix and direct injection systems. May be used in large capacity outboards and is 67% biodegradable according to OECC 301F, making it friendlier to the marine environment than mineral oils.

NMMA Certifiable, TC-W3<sup>®</sup>

*Package and Code:*

2.5L SMOB20025

## MARINE OUTBOARD TWO STROKE OIL

Low smoke oil suitable for use in water cooled outboard engines using both oil-injection and pre-mix fuel systems as well as the new direct injection engines. Mixes readily with petrol.

NMMA Approval Number RL-00419J, TC-W3<sup>®</sup>

*Package and Code:*

1L OUTB001  
20L OUTB020

5L OUTB005  
205L OUTB205

10L OUTB010

## AUTOMATIC TRANSMISSION FLUIDS

All Penrite automatic transmission fluids (ATFs) can be used in cars and trucks where specified. They may also be used as compressor fluids or as power steering fluids where ATFs are specified.

### ATF DX-VI

Synthetic extended drain fluid (400,000km) suitable for all 4, 5 and 6 speed automatics used by Holden in Australian and US built vehicles (GM hydramatic). DEXRON<sup>®</sup>VI Approval

Number J-60312

*Package and Code:*

4L ATFDX6004

20L ATFDX6020

### ATF DX-III

Extended drain fluid suitable for pre 2006 automatics and power steering systems of GM (Holden) vehicles as well as many European and Japanese manufacturers. The upgraded formulation also meets the service fill requirements of BTR 85LE, 91LE and 95LE 4 speed transmissions fitted to Ford passenger cars, from the EAII series Falcon and its derivatives to current.

DEXRON<sup>®</sup>-IIIH (obsolete), MERCON<sup>®</sup>-IV (obsolete), Allison C-4, MB 236.1, BTR 5M-52, M2C 166H

*Package and Code:*

1L ATFDX3001  
60L ATFDX3060

4L ATFDX3004  
205L ATFDX3205

20L ATFDX3020

### ATF MHP

Semi-synthetic automatic transmission fluid for Mitsubishi, Hyundai, Proton and some Kia motor vehicles. Can be used in these vehicles where MM SP, MM SP2, MM SP3 and DEXRON<sup>®</sup>-III fluids are specified. Also suitable for Nissan, Honda and Toyota automatic transmissions and European built Holdens. Upgraded blend is also ideal for European 4/5 speed automatic transmissions.

Mitsubishi MM SP3, Chrysler 7176E (ATF+3<sup>®</sup>/4<sup>®</sup>), Toyota T-II/T-IV/WS, Nissanmatic C, D, J and K, Opel,

MB 236.10/11, LT 71141, ATF 3403, JASO 1A

*Package and Code:*

4L ATFMHP004

20L ATFMHP020

60L ATFMHP060

205L ATFMHP205

### ATF FM5

Fully approved synthetic transmission oil against Ford MERCON<sup>®</sup>-V for warranty service. It is also ideal to upgrade from ATF MHP as a fully synthetic product and can be used in most European and Asian automatic transmissions. Ford License Number M5091006.

Ford M2C-202C, Mitsubishi MM SP3, Chrysler 7176E (ATF+3<sup>®</sup>/4<sup>®</sup>), Toyota T-II/T-IV/WS, Nissanmatic K and S, JASO 1A, Opel, MB

236.10/11, LT 71141, ATF 3403, JASO 1A

*Package and Code:*

4L ATFFM5004

20L ATF FM5020

60L ATF FM5060

205L ATF FM5205

### CVT FLUID V

Special oil for continuously variable transmissions (CVT) that use the Van Doorne belt system such as those found in Nissan, Chrysler, MG, Mercedes Benz, Dodge, Mitsubishi and many others. **Not** suitable for Luk type CVTs as used by Audi (Multitronic).

Nissan NS-2, MB 236.20, Ford **MERCON<sup>®</sup> C**,

*Package and Code:*

4L CVTV004

20L CVTV020



## MANUAL GEAR OIL 75

New Generation technology, semi-synthetic gear oil suitable for use in many modern manual gearboxes where originally an automatic transmission fluid was specified. Can be used where SAE 75W-80 or 80W grades are specified in the handbook. Provides superior cold shift characteristics. SAE 75W-80, API GL-4 Plus, Honda MTF 7389, Land Rover MTF94, MB 235.10

*Package and Code:*

1L MGO7580001	2.5 MGO75800025	20L MGO7580020
60L MGO7580060	205L MGO758 0205	

## MANUAL GEAR OIL 80

Advanced gear oil suitable for modern manual gearboxes and some transaxles where the manufacturer recommends an SAE 80W, 80W-85, 75W-90 or 80W-90 API GL-4 gear oil.

SAE 80W-85, API GL-4, MB 235.5, BTR 5M-42, HN 1820

*Package and Code:*

1L MGO8 085001	2.5L MGO8 0850025	20L MGO8085020
60L MGO8 085060	205L MGO8 085205	

## HYPOLID 80W-90

A hypoid and spiral bevel gear oil ideal for differentials and manual gearboxes of cars and trucks. Mack approved.

SAE 80 W-90, API GL-5, PG-2, MT-1, Mack GO-J, MIL-L-PRF-2105E

*Package and Code:*

1L HYP8090001	2.5L HYP80900025	20L HYP8090020
60L HYP8090060	205L HYP8090205	

## HYPOLID 85W-140

Designed for use in heavy duty or older differentials and where specified by the manufacturer. Mack approved. SAE 85W-140, API GL-5, PG-2, MT-1, Mack GO-J, MIL-L-PRF-2105E

*Package and Code:*

1L HYP85140001	2.5L HYP851400025	20L HYP85140 020
60L HYP85140060	205L HYP85140205	

## HYPOLID 140

For use in large trucks, buses etc. and rear differentials in some recreational 4WDs. Helps quieten worn differentials.

SAE 140, API GL-5, PG-2

*Package and Code:*

20L HYP140020	205L HYP140205
---------------	----------------

## LIMSLIP 90

Limited slip differential oil for vehicles in standard on-road use. Exceeds API GL-5 and the obsolete API GL-6. Contains an initial fill level of limited slip additive.

SAE 80W-90, API GL-5/6, PG-2, MT-1, MIL-L-PRF-2105E

*Package and Code:*

1L LIM90001	2.5L LIM900025	20L LIM90020
60L LIM90060	205L LIM90205	

## LIMSLIP 85W-140

A heavier version of Limslip 90 that can be used in vehicles subjected to extreme temperature or where the vehicle manufacturer recommends this viscosity.

SAE 85W-140, API GL-5/6, PG-2, MT-1, MIL-L-PRF-2105E

*Package and Code:*

1L LIM851400001	2.5L LIM851400025	20L LIM85140020
60L LIM85140 060	205L LIM85140205	

## LIMSLIP 140

Heavy limited slip gear oil suitable for use in some heavy commercial vehicles and 4WDs. SAE 140, API GL-5/6, PG-2

*Package and Code:*

1L LIM140001	2.5L LIM1400025	20L LIM140020	60L LIM140060
--------------	-----------------	---------------	---------------

## LIMSLIP ADDITIVE

Top treat used to alleviate problems associated with chatter in all limited slip and spin resistant differentials.

*Package and Code:*

150ml LSADD000150

## MARINE OUTBOARD GEAR OIL

Semi-synthetic gear oil suitable for most outboard and stern drives units.

SAE 75W-90, API GL-4/5

*Package and Code:*

500ml MAR75900005	20L MAR7590020
-------------------	----------------

## LZ 7906

Top treat used to alleviate shift problems in some GMH and Ford 5 speed manual transmissions that use automatic transmission fluids. Not designed for use with gear oils.

*Package and Code:*

150ml LZ7906000150







## GEAR OIL SYN 220

Premium fully synthetic industrial gear oils suitable for use in applications requiring a low level of EP in industrial and in some automotive applications where long drains or high temperatures are encountered.

*Package and Code:*

<b>ISO</b>	<b>220</b>
20L	GOSYN220020

## ROCKSLIDE

Premium extreme pressure industrial slideway and rock drill oils for air hammers, lathes and as a gear oil where a tacky product is required.

*Package and Code:*

	<b>ISO 68</b>	<b>ISO 320</b>
20L	RS68020	205L RS320205

## HONING OIL

For use in honing machines. Provides long stone life and superior finish to work. Can be used for machining and honing of cast iron, free machining of steel and thread cutting and deep hole drilling of ferrous materials. Made from advanced hydrocracked base stocks.

*Package and Code:*

20L HON020	205L HON205
------------	-------------

## SOLUBLE OIL

General-purpose soluble cutting oil made by using advanced emulsifiers, a bactericide and hydro-cracked base oils for many turning, milling, drilling and grinding operations.

*Package and Code:*

5L SOL005	20L SOL020
-----------	------------

## COMPRESSOR OIL 4KH-46

Synthetic compressor fluid manufactured from the latest ashless additive technology and severely hydrotreated and synthetic base oils. May be used in many reciprocating, rotary vane and centrifugal compressors that require an ISO 46 oil of this type. Contact Penrite for exact details.

*Package and Code:*

20L CO4KH46020
----------------

## CHAINSAW BAR OIL

A premium chain bar oil with an extra clinging ability to protect both chain and bar on chainsaws.

*Package and Code:*

1L CSB001	5LCSB005	20L CSB020	205L CSB205
-----------	----------	------------	-------------

## FUEL SYSTEM PRODUCTS

### UPPER CYLINDER AND LPG LUBRICANT

Dual-purpose product designed for use in LP Gas and dual fuel systems to protect against reduced lubrication due to gas dryness and as an effective injector cleaner in petrol engines. Can be used in dripper systems or added to the fuel at a treat rate of 50ml to 50L of fuel. Note this product darkens if exposed to light.

*Package and Code:*

1L UCL001	4L UCL004
-----------	-----------

## VINTAGE, VETERAN AND CLASSIC LUBRICANTS

### HERITAGE ENGINE OILS

Two engine oils designed to fulfil the requirements of Pre 1920 veteran, Edwardian cars, stationary engines and agricultural machinery fuelled by petrol, kerosene (paraffin) or diesel.

HERITAGE LTM (Light to Medium) and HERITAGE MTH (Medium to Heavy)

*Package and Code:*

	<b>LTM</b>	<b>MTH</b>
5L	HERLTM005	HERMTH005

### SHELSLEY ENGINE OILS

Designed for 1920-1950s era petrol and diesel engines.

SHELSLEY LIGHT is for use where SAE 30 oils were originally recommended, SHELSLEY MEDIUM is for use where SAE 40 oils were originally recommended and SHELSLEY HEAVY is for use where SAE 50 oils were originally recommended.

*Package and Code:*

	<b>LIGHT</b>	<b>MEDIUM</b>	<b>HEAVY</b>
5L	SHELL005	SHELM005	SHELH005
20L	SHELM020		

### CLASSIC ENGINE OILS

Designed for 1950-1970s era petrol and diesel engines.

CLASSIC LIGHT for use where SAE 30 or old style SAE 20W-50 or 20W oils were originally recommended. CLASSIC MEDIUM for use in warmer climates than Classic Light or where SAE 40 oils were originally recommended.

CLASSIC HEAVY for use in high ambient temperatures or where old style SAE 50 oils were originally used. Also ideal in large engined vehicles that may be suffering from oil consumption problems.

*Package and Code:*

	<b>LIGHT</b>	<b>MEDIUM</b>	<b>HEAVY</b>
5L	CLASL005	CLASM005	CLASH005

## GEAR OIL 30 & 40

Two gear oils suitable for classic sports cars, especially those fitted with overdrive gearboxes. Designed for use where the original monogrades engine oils were recommended in gearboxes.

*Package and Code:*

	30	40
1L	GB30001	GB40001

## MILD EP GEAR OIL

An API GL-4 rated gear oil for use in worm differentials, pre 1960 hypoid differentials and motorcycle shaft drives. Will not cause corrosion to bronze components. Do not use if exposure to water is likely.

*Package and Code:*

1L MILD001

## TRANSOIL 90, 140, 250

A series of API GL-1 rated monograde gear oils for use in veteran, Edwardian and vintage gearboxes and final drives. These oils do not corrode ferrous and non-ferrous materials and are compatible with leather and synthetic rubber seals. Do not use Transoil 250 if exposure to water/steam is likely.

*Package and Code:*

SAE	90	140	250
1L	T90001	T140001	T250001

## SU DASHPOT & SU DAMPER OIL

Specifically developed to lubricate dash pots and dampers of SU carburettors.

*Package and Code:*

150ml SUDASH000150 SUDAMP000150

## SHOCKER OIL 1 & 2

Series of oils for use in lever arm type shock absorbers and motorcycle forks that need SAE 20 or 30 type oils.

*Package and Code:*

1L SHOK1001 SHOK2001

## WATER PUMP GREASE

A heavy NLGI No. 4 calcium-based moderate-duty grease for automotive water pumps in older vehicles, fire fighting and irrigation equipment.

*Package and Code:*

50g WPG00005

## SEMI FLUID GREASE

NLGI 00 semi fluid grease. Ideal for veteran car transmissions and for veteran and vintage motorcycle gearboxes such as the Burman.

*Package and Code:*

450g SEMI00045

## STEERING BOX LUBRICANT

A high viscosity "self-levelling" grease containing non-corrosive extreme pressure additives to provide film strength. Suitable for veteran/vintage and some classic car steering boxes.

*Package and Code:*

450g SBL00045

## CLASSIC CAR COOLANT CONCENTRATE

A non-glycol, undyed hybrid conventional/organic inhibitor designed to protect cooling systems from electrolysis and oxidation. Product does not become corrosive or change the cooling characteristics of water. 3 years protection when used and maintained at 12% concentration.

*Package and Code:*

1L VCI001

Further information on Penrite Products can be found in the Product Information Sheets. Please feel free to contact us or log on to our web page.

PENRITE OIL COMPANY PTY LTD  
88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152  
ABN 25 005 001 525  
Enquiries: Phone 1300-PENRITE (1300 736 7483)  
Fax: 1800-PEN RITE (1800 736 7483)

International: Phone: 61 3 9801 0877 Fax: 61 3 9801 0977

[www.penriteoil.com](http://www.penriteoil.com)

**A Better Class of Oil**

[www.penriteoil.com.au](http://www.penriteoil.com.au)

Penrite Oil Company Pty Ltd

Ph: 1300 PENRITE (1300 736 748)

Int: 61 3 980 1 0877

Email: [penrite@penriteoil.com](mailto:penrite@penriteoil.com)

ABN 25 005 001 525



## **PREMIUM CLASS CARNAUBA WAX**

High quality protectant for new and nearly new paintwork. Protects against adverse weather and other environmental hazards, reduces adhesion of insects. Visible water run off effect. The highly concentrated carnauba wax maintains and protects the paint lacquer and provides a dazzling high gloss. The new formula is easily polished out without leaving greasy streaks. Pack contains an application pad and quality Sonax Micro fibre cloth

*Package and Code:*  
200 ml 211200

## **PREMIUM CLASS PAINTWORK CLEANER**

Paintwork Cleaner is the optimum preparation of the paintwork for a subsequent sealing. It degreases the paintwork and removes smear films caused by silicone, oil and wax deposits. It polishes out fine scratches, smoothens the paintwork and enhances the shine. Follow application with Sonax Premium Carnauba Wax to seal and protect paintwork. Pack contains an application pad and quality Sonax Micro fibre cloth

*Package and Code:*  
250 ml 212200

## **ABRASIVE PASTE**

Ideal for weathered and dull paint. Smooths out and removes scratches, spray paint residue. Prepares a suitable base for re-spray work.

*Package and Code:*  
1L 320300

## **FINE ABRASIVE PASTE**

Polish for specialist use in paint shops and for used car valeting. Use with a speed regulating polishing machine. Removes occluded dust, paint overspray, abrasion traces. Ideal for the restoration of weathered and scratched paintwork. High abrasion with simultaneous medium gloss effect.

*Package and Code:*  
1L 319300

## **ABRASIVE POLISH**

Polish containing a high proportion of abrasives. Formulated to remove faults after repainting jobs (dust inclusion, colour haze, abrasive tracks) or for valeting of weather-worn or scratched paintwork. Maybe applied manually or with polishing machine. Wax and silicone-free.

*Package and Code:*  
1L 285300

## **NANO POLISH**

Silicone-free polish for all types of paintwork. Ideal for the care and maintenance of scratch resistant varnishes. New paintwork is gently made to shine. Matt and scratched paintwork can be quickly and easily treated and even scratch resistant varnishes can be polished professionally and hologram-free. Wax and silicone-free.

*Package and Code:*  
1L 208300

## **NANO POLISH & WAX**

Silicone-free polish for all types of paintwork. Silicon-free polish with nano abrasive granules for professional machine polishing of nearly new up to slightly scratched paints, also paints which have been pre-polished with SONAX Abrasive Polish. Carnauba wax ensures a hologram-free, deep shine finish with simultaneous wax protection. Very easy to work in.

*Package and Code:*  
1L 207300

## **WHEEL AND TYRE CARE**

### **RUBBER PROTECTANT/CARE**

Cleans and cares for rubber parts and keeps them elastic. Tyres and floor mats are easily cleaned and original fresh appearance restored. Satin finish dries in seconds not minutes. Spray on and wipe over with an application sponge.

*Package and Code:*  
300 ml 3402000

5L 340505

### **XTREME TYRE GLOSS GEL**

The innovative gel formula maintains and, at the same time, protects rubber and tyres against cracking and colours against fading. Lasts for several weeks. Available as set with application sponge or as single bottle.

*Package and Code:*  
500 ml 235200-755







## **MICRO FIBRE CLOTH 2 PACK**

High quality, fleecy Microfibre Cloth for removing polish residues. It also removes silicone and wax smears left behind after polishing and produces a dazzling, deep shine without leaving scratches, streaks or clouds on the paintwork. Lint free and washable.

*Package and Code:*  
416241

## **FORD CAR CARE RANGE**

### **FORD PREMIUM SHAMPOO**

Extremely economical concentrate for fast and thorough cleaning. Gently dissolves even the most stubborn dirt. Clear Coat safe and phosphate free.

*Package and Code:*  
500ml 214200-720

### **FORD PREMIUM WAX**

Liquid wax based on nano-technology, for use on all standard, metallic and scratch resistant paints. Microfine carnauba wax particles ensure a deep mirror shine and long lasting protection. Nano technology makes it extremely easy to polish out.

*Package and Code:*  
500ml 201200-720

### **FORD HIGH GLOSS POLISH**

Polish based on nano-technology and safe on all paint surfaces. Rejuvenates colours and produces a dazzling deep shine. Nano fine abrasive particles smoothen the top paint layer and the high quality carnauba wax protects the paintwork for several weeks. Extremely easy to polish out and removes car-wash brush marks

*Package and Code:*  
500ml 202200-720

### **FORD INTERIOR CLEANER**

Powerful cleaning solution for the removal of stubborn dirt from carpets, upholstery, textiles, floor coverings and use as a pre-treat for heavily soiled leather upholstery. Penetrates deep into fibres and refreshes colours.

*Package and Code:*  
500ml 321200-720

### **FORD GLASS CLEANER**

Removes dirt, dust and exhaust residue from windows, headlights and mirrors. The foam sticks to the dirt and works very intensely. Leaves no streaks. Also suitable for use in the car interior.

*Package and Code:*  
300 ml 374200-720

### **FORD DASH PROTECTANT**

Cleans and cares for all plastic parts in the car interior. Reliably prevents electrostatic charges and is therefore dust repellent. Renews and maintains the matt and structured surface. Leaves pleasant and fresh scent behind. Silicone-free

*Package and Code:*  
300 ml 283200-720

### **FORD WHEEL CLEANER**

Highly effective acid-free special cleaner for all types of steel and alloy wheels. Easily removes even the most stubborn dirt such as burnt on brake dust, oil and rubber residue and other road dirt. Extremely easy to use. *Package and Code:*

500 ml 230200-720

**A Better Class of Oil**

[www.penriteoil.com.au](http://www.penriteoil.com.au)

Penrite Oil Company Pty Ltd  
Ph: 1300 PENRITE (1300 736 748)  
Int: 61 3 980 1 0877  
Email: [penrite@penriteoil.com](mailto:penrite@penriteoil.com)

ABN 25 005 001 525